

Prefabricated Branch Cables

0.6/1kV Single-Core

XLPE Insulated, Unarmoured, PVC Sheathed Cable

Description: AL/XLPE/PVC

Model Code: AXP



tel (65) 6367 0107 fax (65) 6365 2963

www.keystone-cable.com



| | | |
|-------------------------|--|--|
| Application : | This cable is used in power supply and distribution system for high-rise residential, commercial buildings, hotels, and factories. | |
| Voltage rating : | 0.6/1kV | |
| Construction : | Aluminium conductor (IEC 60228 Class 2), XLPE insulated, unarmoured, PVC compound sheathed cable | |
| Insulation colour : | Natural | |
| Sheath colour : | Black | |
| Specification : | IEC 60502-1, IEC 60332-1-2 | |
| Operating temperature : | 90°C | |

| Nominal Area (mm ²) | Conductor | | Thickness (mm) | Part No. | Unarmoured Cable | |
|------------------------------------|------------------------------------|--------------------------|-------------------|-----------|----------------------------------|------------------------------|
| | No./Diam. of Strand (no./mm) | Approx. Diam. (mm) | | | Approx. Overall Diam. (mm) | Approx. Weight (kg/km) |
| 25 (cs) | 7/2.16 | 6.0 | 0.9 | 1301B**** | 11.2 | 170 |
| 35 (cs) | 7/2.50 | 7.0 | 0.9 | 1401B**** | 12.1 | 215 |
| 50 (cs) | 7/2.90 | 8.3 | 1.0 | 1501B**** | 13.6 | 265 |
| 70 (cs) | 19/2.16 | 10.0 | 1.1 | 1601B**** | 15.6 | 345 |
| 95 (cs) | 19/2.50 | 11.5 | 1.1 | 1701B**** | 17.6 | 440 |
| 120 (cs) | 19/2.80 | 13.0 | 1.2 | 1801B**** | 19.3 | 530 |
| 150 (cs) | 19/3.15 | 14.5 | 1.4 | 1901B**** | 21.3 | 650 |
| 185 (cs) | 36/2.54 | 16.2 | 1.6 | 2001B**** | 23.6 | 785 |
| 240 (cs) | 36/2.90 | 18.3 | 1.7 | 2101B**** | 26.0 | 980 |
| 300 (cs) | 36/3.30 | 20.6 | 1.8 | 2201B**** | 28.7 | 1200 |
| 400 (cs) | 60/2.92 | 23.7 | 2.0 | 2301B**** | 32.4 | 1520 |
| 500 (cs) | 60/3.30 | 26.7 | 2.2 | 2401B**** | 36.1 | 1890 |
| 630 (cs) | 60/3.75 | 30.3 | 2.4 | 2501B**** | 40.5 | 2395 |
| 800 (cs) | 60/4.30 | 34.0 | 2.6 | 2601B**** | 44.8 | 2980 |
| 1000 (cs) | 60/4.70 | 37.8 | 2.8 | 2701B**** | 49.2 | 3690 |

**** Stands for branch size, please contact us for more information.

Current rating and voltage drop

Please refer to Table 1 & 2 (Page 25)

(cs) : Circular Compact Stranded Conductor

Current Rating and Voltage Drop

XLPE Insulated Cables
Single-Core, Aluminium Conductors



tel (65) 6367 0107 fax (65) 6365 2963
www.keystone-cable.com

Single-Core Cables with XLPE Insulation, with PVC (or LSZH) Outersheath 0.6/1kV

Table 1 : Current-Carrying Capacities (Amp)

[AL/XLPE/PVC or AL/XLPE/LSZH Cables]

Conductor Operating Temperature : 90°C

Ambient Temperature : 30°C

IEC 60502-1

| Conductor Cross-sectional Area | Reference Method 4 (enclosed in conduit in thermally insulating wall etc) | | Reference Method 3 (enclosed in conduit on a wall or in trunking etc) | | Reference Method 1 (clipped direct) | | Reference Method 11 (on a perforated cable tray, horizontal or vertical) | | Reference Method 12 (in free air) | | |
|--------------------------------|---|-----------------------------|---|-----------------------------|--|--|--|--|---|---|---------|
| | 2 cables, 1-phase a.c. or d.c. | 3 or 4 cables, 3-phase a.c. | 2 cables, 1-phase a.c. or d.c. | 3 or 4 cables, 3-phase a.c. | 2 cables, 1-phase a.c. or d.c. flat and touching | 3 or 4 cables, 3-phase a.c. flat and touching or trefoil | 2 cables, 1-phase a.c. or d.c. flat and touching | 3 or 4 cables, 3-phase a.c. flat and touching or trefoil | 2 cables, 1-phase a.c. or d.c. or 3 cables 3-phase a.c. | 2 cables, 1-phase a.c. or d.c. or 3 cables 3-phase a.c. | Trefoil |
| mm ² | A | A | A | A | A | A | A | A | A | A | A |
| 50 | 125 | 113 | 157 | 140 | 169 | 149 | 180 | 165 | 210 | 188 | 159 |
| 70 | 158 | 142 | 200 | 179 | 215 | 189 | 231 | 211 | 271 | 244 | 206 |
| 95 | 191 | 171 | 242 | 217 | 265 | 234 | 281 | 258 | 332 | 300 | 253 |
| 120 | 220 | 197 | 281 | 251 | 308 | 273 | 326 | 300 | 387 | 351 | 296 |
| 150 | 253 | 226 | - | - | 353 | 314 | 376 | 346 | 448 | 408 | 343 |
| 185 | 288 | 256 | - | - | 340 | 366 | 430 | 396 | 515 | 470 | 395 |
| 240 | 338 | 300 | - | - | 489 | 438 | 509 | 469 | 611 | 561 | 471 |
| 300 | 387 | 344 | - | - | 564 | 507 | 586 | 541 | 708 | 652 | 544 |
| 380 (400) | - | - | - | - | 658 | 594 | 679 | 628 | 798 | 742 | 638 |
| 480 (500) | - | - | - | - | 765 | 692 | 786 | 728 | 927 | 865 | 743 |
| 600 (630) | - | - | - | - | 871 | 791 | 903 | 836 | 1058 | 990 | 849 |
| 740 (800) | - | - | - | - | 1001 | 911 | 1025 | 951 | 1218 | 1143 | 979 |
| 960 (1000) | - | - | - | - | 1176 | 1072 | 1191 | 1108 | 1440 | 1355 | 1151 |

Note : For rating factors of ambient temperature other than 30°C, please refer to Table 9 (Page 29)

Table 2 : Voltage Drop (Per Amp Per Meter)
[AL/XLPE/PVC or AL/XLPE/LSZH Cables]

Conductor Operating Temperature : 90°C

IEC 60502-1

| Conductor Cross-sectional Area | 2 cables, d.c. | 2 cables, 1-phase a.c. | | | | | | 3 or 4 cables, 3-phase a.c. | | | | | | | | |
|--------------------------------|----------------|--|------|------|--|-------|------|--|------|-------|--|-------|-------|--|------|------|
| | | Reference Methods 3 and 4 (enclosed in conduit etc, in or on a wall) | | | Reference Methods 1 and 11 (clipped direct or on trays touching) | | | Reference Methods 3 and 4 (enclosed in conduit etc, in or on a wall) | | | Reference Methods 1, 11 and 12 (trefoil) | | | Reference Methods 1 and 11 (flat and touching) | | |
| | | 1 | 2 | 3 | 4 | 5 | 6 | 7 | r | x | z | r | x | z | r | x |
| mm ² | mV/A/m | mV/A/m | | | mV/A/m | | | mV/A/m | | | mV/A/m | | | mV/A/m | | |
| | | r | x | z | r | x | z | r | x | z | r | x | z | r | x | z |
| 50 | 1.65 | 1.70 | 0.30 | 1.72 | 1.65 | 0.190 | 1.66 | 1.44 | 0.26 | 1.46 | 1.44 | 0.165 | 1.45 | 1.44 | 0.24 | 1.46 |
| 70 | 1.13 | 1.17 | 0.30 | 1.21 | 1.12 | 0.185 | 1.14 | 1.00 | 0.26 | 1.04 | 0.97 | 0.160 | 0.98 | 0.97 | 0.24 | 1.00 |
| 95 | 0.82 | 0.86 | 0.29 | 0.91 | 0.82 | 0.185 | 0.84 | 0.75 | 0.25 | 0.79 | 0.71 | 0.160 | 0.73 | 0.71 | 0.23 | 0.75 |
| 120 | 0.65 | 0.68 | 0.29 | 0.74 | 0.65 | 0.180 | 0.67 | 0.59 | 0.25 | 0.64 | 0.57 | 0.155 | 0.59 | 0.57 | 0.23 | 0.61 |
| 150 | 0.53 | 0.54 | 0.28 | 0.61 | 0.52 | 0.175 | 0.55 | 0.48 | 0.24 | 0.54 | 0.45 | 0.155 | 0.47 | 0.45 | 0.23 | 0.50 |
| 185 | 0.42 | 0.45 | 0.28 | 0.53 | 0.43 | 0.175 | 0.46 | 0.38 | 0.24 | 0.45 | 0.36 | 0.150 | 0.39 | 0.36 | 0.23 | 0.43 |
| 240 | 0.32 | 0.34 | 0.27 | 0.43 | 0.32 | 0.170 | 0.36 | 0.30 | 0.24 | 0.38 | 0.28 | 0.150 | 0.32 | 0.28 | 0.22 | 0.35 |
| 300 | 0.26 | 0.28 | 0.27 | 0.38 | 0.26 | 0.170 | 0.31 | 0.25 | 0.23 | 0.34 | 0.22 | 0.145 | 0.27 | 0.22 | 0.22 | 0.31 |
| 380 (400) | 0.20 | - | - | - | 0.21 | 0.165 | 0.27 | 0.20 | 0.23 | 0.31 | 0.180 | 0.145 | 0.23 | 0.180 | 0.22 | 0.28 |
| 480 (500) | 0.160 | - | - | - | 0.170 | 0.165 | 0.23 | 0.165 | 0.23 | 0.28 | 0.150 | 0.140 | 0.20 | 0.150 | 0.22 | 0.27 |
| 600 (630) | 0.130 | - | - | - | 0.140 | 0.160 | 0.21 | 0.135 | 0.22 | 0.26 | 0.120 | 0.140 | 0.185 | 0.120 | 0.22 | 0.25 |
| 740 (800) | 0.105 | - | - | - | 0.115 | 0.160 | 0.19 | - | - | 0.100 | 0.135 | 0.170 | 0.100 | 0.21 | 0.23 | |
| 960 (1000) | 0.080 | - | - | - | 0.092 | 0.155 | 0.18 | - | - | 0.082 | 0.135 | 0.160 | 0.082 | 0.21 | 0.23 | |

Note : r = resistive component; x = reactive component; z = impedance value

Technical Information



tel (65) 6367 0107 fax (65) 6365 2963
www.keystone-cable.com

Table 9 : Correction Factor for Ambient Air Temperature Other than 30°C to be Applied to the Current-Carrying Capacities for Cables in Free Air

| Insulation | Ambient Temperature (°C) | | | | | | | | | | | | | | | |
|-------------|--------------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| | 10 | 15 | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | 65 | 70 | 75 | 80 | 85 |
| XLPE (90°C) | 1.15 | 1.12 | 1.08 | 1.04 | 1.00 | 0.96 | 0.91 | 0.87 | 0.82 | 0.76 | 0.71 | 0.65 | 0.58 | 0.50 | 0.41 | 0.29 |

Table 10 : Correction Factor for Ambient Ground Temperature Other Than 15°C to be Applied to the Current-Carrying Capacities for Cables in Ducts or in Ground

| Insulation | Ground Temperature (°C) | | | | | | | | | | | |
|-------------|-------------------------|------|------|------|------|------|------|------|------|------|------|------|
| | 10 | 15 | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | 65 |
| XLPE (90°C) | 1.03 | 1.00 | 0.97 | 0.93 | 0.89 | 0.86 | 0.82 | 0.77 | 0.73 | 0.67 | 0.63 | 0.58 |

Table 11 : Correction Factors for Ambient Temperature & Group Installation

Correction for groups of more than one circuit of single-core cables, or more than one multi-core cable

| Reference Methods of Installation | Correction Factor (Cg) | | | | | | | | | | | | | |
|--|---|------|------|------|------|------|------|------|------|------|------|------|------|------|
| | Number of Circuits or Multi-Core Cables | | | | | | | | | | | | | |
| | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 12 | 14 | 16 | 18 | 20 |
| Enclosed (Method 3 or 4) or bunched and clipped to a non-metallic surface (Method 1) | 0.80 | 0.70 | 0.65 | 0.60 | 0.57 | 0.54 | 0.52 | 0.50 | 0.48 | 0.45 | 0.43 | 0.41 | 0.39 | 0.38 |
| Single layer clipped to a non-metallic surface (Method 1) | Touching | 0.85 | 0.79 | 0.75 | 0.73 | 0.72 | 0.72 | 0.71 | 0.70 | - | - | - | - | - |
| | Spaced* | 0.94 | 0.90 | 0.90 | 0.90 | 0.90 | 0.90 | 0.90 | 0.90 | 0.90 | 0.90 | 0.90 | 0.90 | 0.90 |
| Single layer multi-core on a perforated metal cable tray (Method 11) | Touching | 0.86 | 0.81 | 0.77 | 0.75 | 0.74 | 0.73 | 0.73 | 0.72 | 0.71 | 0.70 | - | - | - |
| | Spaced* | 0.91 | 0.89 | 0.88 | 0.87 | 0.87 | - | - | - | - | - | - | - | - |
| Single layer single-core on a perforated metal cable tray, touching (Method 11) | Horizontal | 0.90 | 0.85 | - | - | - | - | - | - | - | - | - | - | - |
| | Vertical | 0.85 | - | - | - | - | - | - | - | - | - | - | - | - |
| Single layer multi-core touching on ladder supports | | 0.86 | 0.82 | 0.80 | 0.79 | 0.78 | 0.78 | 0.78 | 0.77 | - | - | - | - | - |

* Space means a clearance between adjacent surfaces of at least one cable Diam. (D^o). Where the horizontal clearance between adjacent cables exceeds $2 D^o$, no correction factor need be applied

Note : 1 The factors in the table are applicable to a group of cables all of the same sizes. The value of the current derived from application of the appropriate factors is the maximum continuous current to be carried by any of the cables in the group.

2 If, due to known operating conditions, a cable is expected to carry not more than 30% of its grouped rating, it may be ignored for the purpose of obtaining the rating factor for the rest of the group.

For example, a group of N loaded cables would normally require a group reduction factor of Cg applied to the tabulated Lt. However, if M cables in the group carry loads which are not greater than $0.3Cg Lt$ amperes, the other cables can be sized by using the group rating factor corresponding to $(N-M)$ cables.